

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 April 2004 (01.04.2004)


PCT

(10) International Publication Number
WO 2004/026598 A1

- (51) International Patent Classification⁷: **B60D 1/52**, 1/14 (74) Agent: **FERGUSON, Alexander**; Octrooibureau Vriesendorp & Gaade, P.O. Box 266, NL-2501 AW The Hague (NL).
- (21) International Application Number: PCT/NL2003/000645
- (22) International Filing Date: 17 September 2003 (17.09.2003)
- (25) Filing Language: Dutch
- (26) Publication Language: English
- (30) Priority Data: 1021479 17 September 2002 (17.09.2002) NL
- (71) Applicant (for all designated States except US): **BRINK INTERNATIONAL B.V.** [NL/NL]; P.O. Box 24, NL-7950 AA Staphorst (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **LIER, Johan** [NL/NL]; P.O. Box 24, NL-7950 AA Staphorst (NL). **HEMSTEDE, Gerrit, Albartus** [NL/NL]; P.O. Box 24, NL-7950 AA Staphorst (NL).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES (utility model), FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: COUPLING ASSEMBLY FOR VEHICLES



(57) Abstract: Coupling assembly (1) for vehicles, comprising a vehicle, the coupling assembly (1) comprising a first coupling member (20) provided with a connection member for a car trailer or an accessory, such as a bike rack, and a second coupling member (5) with which the first coupling member can be coupled to connect it to the vehicle, the vehicle comprising a chassis (100) having a transverse beam (4) situated at the rear side of the vehicle, the second coupling member (5) being permanently or undetachably attached to the transverse beam (4).

**Declaration under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE,

DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Coupling assembly for vehicles

The invention relates to a coupling assembly for vehicles, such as for a tow hitch facility.

Coupling assemblies for vehicles have been generally known and for quite some time already. Usually the coupling assemblies are adjusted to use for towing car trailers, by means of a tow hitch. Such assemblies used to be permanent, but later on two-part tow hitch assemblies were brought onto the market consisting of an accommodation part that was permanently attached to the vehicle and a detachable tow hitch member, that could be
10 coupled into the accommodation part for use, and after use could be uncoupled in order to be stowed away. In that way the tow hitch, when inoperative, does not constitute an obstacle to persons passing the vehicle at the rear. Moreover it is not allowed that the hitch ball fully or partially covers the license plate.

15

An example of such a tow hitch assembly is described in European patent application 0.950.549 the contents of which should be deemed included here.

20

In the existing tow hitch assemblies that can be uncoupled, the accommodation part is attached to the new or old vehicle by means of a transverse beam, which extends at the front below the rear bumper and at the ends and at intermediate locations is attached to the rear side of the chassis of the vehicle.

25

The existing tow hitch assemblies -that may or may not be uncouplable-

increase the standard weight of the vehicle, particularly as a result of transverse beam. The transverse beam hanging behind the chassis may form a protruding hindrance when the rear side of the vehicle passes over the ground.

5

Another drawback of the existing tow hitch assemblies is that they require a lot of mounting operations, which particularly renders the fitting of a tow hitch assembly at a later stage, expensive.

10 It is an objective of the invention to improve on this.

From one aspect the invention to that end provides an assembly of a vehicle and a coupling assembly for it, the coupling assembly comprising a first coupling member provided with a connection member for a car trailer or an
15 accessory, such as a bike rack, and a second coupling member with which the first coupling member can be coupled to connect it to the vehicle, the vehicle comprising a chassis having a transverse beam situated at the rear side of the vehicle, the second coupling member being permanently or undetachably attached to the transverse beam.

20

Due to the integration of the permanently vehicle-fixed second coupling member with the supporting structure of the vehicle, particularly the chassis transverse beam, the usual additional transverse beam for mounting the tow hitch assembly can be dispensed with. This results in a weight reduction.
25 The second coupling member can easily (easily accessible, because of at the building stage of the vehicle) and serially be secured. The vehicle is as it were "tow hitch prepped", the consumer can then buy the desired accessory, such as a hitch ball, at a moment that suits him or her. Particular mounting activities are no longer necessary then. Due to the early integration
30 of the second coupling member, the strength of the chassis transverse beam can be utilised -possibly after adjusted design- for the transfer of forces during use.

The quantity of the stock to be kept by the dealer can be kept limited, as only one part of the coupling assembly has to be kept available.

- 5 Preferably the second coupling member is welded fixed to the transverse beam.

Preferably the second coupling member is placed in the transverse beam, as a result of which the occupation of space can be kept very limited.

10

Preferably the transverse beam is tubular having a first wall and an opposite second wall, the second coupling member being permanently or undetachably attached, such as by means of welding, to the first wall and/or to the second wall. In case of attachment to both walls the forces during use can be transferred to the chassis beam at two -in cross-section- spaced apart locations.

15

The first wall and the second wall of the tubular transverse beam may form an upper wall and a lower wall, respectively, of the transverse beam.

20

Advantageously the second coupling member is provided with a placement flange, as a result of which the mounting of the second coupling member is facilitated. If the second coupling member is a steel casting the flange shortens the decarbonization path after casting the second coupling member, which decarbonization is necessary in order to render the material fit for welding.

25

The second coupling member may furthermore be provided with an eye for a hauling or towing cable, by which means several facilities may be placed in one go: separately arranging a towing eye is no longer necessary. Moreover use can be made of the strength of the location of transfer of forces for the hitch ball and the like on the chassis.

30

In the tubular design of the transverse beam a third wall connecting the first and second wall of the transverse beam can be provided with an opening for access to the eye, the eye preferably extending at least partially through the opening to the outside. Here as well space can be saved on.

The second coupling member preferably is furthermore provided with one or more means for attachment of a safety cable, so that they have been present ever since the production of the vehicle.

Preferably the first coupling member can be detachably coupled to the second coupling member, so that it is possible to change the first coupling member.

Preferably the first coupling member is dividable into a first part that can be coupled to the second coupling member and a second part that can be connected to an operation member, such as a hitch ball. Thus the coupling assembly becomes more versatile, and the user is able to choose the wanted function by only selecting a small part of the assembly.

In a further development thereof, the second part is plate-shaped and provided with holes for bolts for attachment of the operation member. As a result many different selected operation members provided with an attachment plate can be used, and attached at a desired height.

In an alternative further development the second part defines an accommodation sleeve for accommodation of an insertion member of the operation member. As a result many different selected operation members provided with an attachment rod can be used, and attached at a desired height.

The second coupling member can be made of steel, particularly metal, and obtained by injection moulding. In this way the wanted shape can easily be

achieved, with the desired strength.

5 In a further development the first coupling member may comprise an insertion member and the second coupling member comprises an accommodation member, in which the insertion member can be coupled in the accommodation member. In this way a stable coupling can be realised.

10 The invention furthermore provides a coupling assembly suitable and intended for an assembly according to the invention.

From a further aspect the invention provides a vehicle having a chassis, the chassis being provided with a coupling member that is permanently fixed and undetachably connected to it, for detachable coupling to a further coupling member for a connection member for an accessory, such as a car trailer or
15 bike rack, to be taken along by the vehicle, such as by towing or carrying.

Preferably the chassis comprises a transverse beam situated at the rear, the coupling member being fixedly attached, preferably welded fixed, to the transverse beam. The coupling member may be welded fixed to the
20 transverse beam using a placement flange that forms a unity therewith.

Preferably the transverse beam is tubular and the coupling member extends into the transverse beam. The transverse beam may be polygonal in cross-section, the coupling member being permanently or undetachably attached to
25 at least two of the sides of the polygon.

From a further aspect the invention provides a coupling member suitable and intended for a coupling assembly or vehicle according to the invention.

30 From a further aspect the application provides an assembly of a vehicle and a coupling assembly for it, the coupling assembly being provided with an eye for a hauling or towing cable. In that way it is possible to simultaneously in

one go, together with the attachment of the coupling assembly, particularly with a tow hitch, provide such an eye on a vehicle.

Further efficiency is achieved when the coupling assembly is furthermore
5 provided with one or more means for attaching a safety cable.

Preferably the coupling assembly comprises a first coupling member provided with a connection part for a car trailer or an accessory, such as a bike rack, and a second coupling member with which the first coupling member can be
10 coupled in order to connect it to the vehicle, the eye and/or means for attaching a safety cable forming a unity with the second coupling member.

Transfer of forces onto the eye and the like is enhanced when the vehicle comprises a chassis having a transverse beam situated at the rear side of the
15 vehicle, the second coupling member being permanently or undetachably connected to the transverse beam.

The application furthermore relates to a coupling assembly for vehicles, provided with one or more measures as described above, particularly the eye
20 for a hauling cable.

The invention will be elucidated on the basis of an exemplary embodiment shown in the attached drawings, in which:

25 Figure 1 shows a schematic inclined view of the rear side of a chassis of an automobile, in which a coupling assembly according to the invention has been incorporated;

Figure 1A shows a detail of a coupling assembly substantially as shown in
30 figure 1, with uncoupled operation member;

Figure 1B shows a straight rear view of the arrangement of figure 1;

Figure 2 shows a view in perspective of the permanent coupling member of the coupling assembly of figure 1;

Figures 3A and 3B show a first embodiment of an operation member for a coupling assembly according to the invention;

Figure 4A and 4B show a second example of an operation member for a coupling assembly according to the invention; and

Figure 5A and 5B show (a part of) another operation member for a coupling assembly according to the invention.

15 Figure 1 shows a chassis 100 of a vehicle, chassis 100 comprising longitudinal beams 101 and a centrally situated transverse beam 4. The transverse beam 4 is made of steel and has a tubular profile having inner space 3.

20 At the chassis transverse beam 4 a preferred embodiment of a coupling assembly 1 according to the invention has been attached. The coupling assembly 1 consist of an accommodation member 5, which is permanently attached to the chassis transverse beam 4 and which is made of cast steel, and, by way of example, an operation member 20 that can be detachably coupled in said accommodation member.

25 As can be seen in figure 1A and figure 2, the accommodation member 5 is hollow, having a tubular portion 8 and below it an accommodation space 6 in which the coupling end of an operation member that is not shown in these figures can be inserted. The accommodation member 5 is formed as one
30 unity with a towing eye 11, having a continuous opening 12 for attaching a towing cable or the like.

The accommodation space 6 has accommodation slits 6b in two opposite walls, which accommodation slits 6b end blindly at the location of 6a. Said grooves are intended for the fitting accommodation of an insertion member of the operation member, as can also be seen in European patent 950.549.

5

At the location of upper edge 9 of the tubular portion 8, the accommodation member 5 is welded fixed to upper wall 4a of chassis transverse beam 4 by means of circumferential weld seam 10a.

10 Around the accommodation part 6 the accommodation member 5 is provided with a circumferential flange 7, which by means of circumferential weld 10b is welded fixed to lower wall 4b of the chassis transverse beam 4. Instead of welding, depending on the materials used, glue can also be used in order to realise the wanted permanent, undetachable connection.

15

Note that the circumferential flange 7 in the figures 1 and 1B is buckled at the rear side, in order to fit on the rear wall 4c that is also buckled. In the rear wall 4c the chassis transverse beam 4 has been provided with a broad recess 2c, through which the towing eye can extend.

20

For inserting the coupling member 5 into the inner space 3, the coupling member 5 is inserted from below into a suitably broad hole 2b, the tubular portion 8 coming first, until the flange 7 abuts the lower surface of the lower wall 4b. The tubular portion 8 with upper edge 9 then fittingly extends into the hole 2a. Then the welds 10a and 10b are made. Despite the broad hole 2a the flange 7 provides sufficient engagement with the wall 4b.

25

It is also possible to use a two-part design of the chassis transverse beam 4, the lower wall 4b belonging to a first, lower part and the upper wall 4a belonging to an upper part to be placed and welded fixed thereon. The coupling member with the flange 7 is then first placed against the lower wall 4b, the weld 10b is made, and subsequently the upper part with upper wall

30

4a is placed, the upper edge 9 of the tubular portion 8 fitting in hole 2a. After that the circumferential weld 10a is made. At locations that are not further shown, both parts of the chassis transverse beam 4 are welded to each other, to form a rigid unity.

5

Thus the coupling member 5 forms one rigid and strong unity with the chassis transverse beam 4. Forces of the coupling assembly, or a cable attached to a towing eye 11 are directly transferred to the chassis transverse beam 4 via the coupling member 5.

10

As is also shown in figure 2, the accommodation member 5, at a location below the flange 7, is provided with eyes 13, for attachment of safety cables, with which for instance a car trailer can be secured, parallel to the coupling line.

15

In figures 3A and 3B an operation member 20 is shown which is used a lot on the European continent. The operation member 20 is a tow hitch member here, having an insertion end 21 that can be detachably coupled in accommodation part 6 of coupling member 5. Use is made here of coupling pins 25 and 26, and operation knob 24. The tow hitch member 20 furthermore has a ball 23, as is customary.

20

The tow hitch member 30 shown in figures 4A and 4B, as regards the insertion member and its operation, corresponds to the tow hitch member of figures 3A and 3B. The tow hitch member 30, however, is divided at the location of plate 35, which is provided with a number of series of holes 37. The actual tow hitch part is provided with a plate 36 having two holes 37, which depending on the desired height are aligned with the holes 37 in plate 36. In that position both members are secured to each other by means of bolts 38. It is possible here to replace the tow hitch part by another accessory, for instance an accessory for carrying a bike rack.

25
30

In figures 5A and 5B a so-called American variety is shown, in which the tow hitch member 40 can also be divided, as shown in figure 5B. The insertion member 41 is first of all designed to be permanently accommodated in accommodation member 5 of figure 1A, which coupling can however take place at a moment that suits the consumer. Alternatively the member 40 can also be provided with uncoupling means.

In the mounted position, the member 40 has plates 42 extending forward and downward in an inclined manner, at the lower end of which a tube section 44 has been attached. The tube section 44 defines an accommodation space 45 for an elongatedly formed tow hitch member 47, which is provided with a continuous hole 49 and with a hitch ball 48. The passage 49 comes in line with passage 46 in the tube member 44, so that a locking pin (not shown) can be inserted into it to secure the tow hitch member 47 to the member 41. By removal of the pin the tow hitch member 47 can be removed again.

Because the chassis transverse beam 4 has already been provided in the factory with an accommodation member 1 for an operation member (of whatever function) the consumer only needs to buy a part of the total coupling assembly and moreover specialised mounting operations can be dispensed with.

Claims

1. Assembly of a vehicle and a coupling assembly for it, the coupling assembly comprising a first coupling member provided with a connection member for a car trailer or an accessory, such as a bike rack, and a second coupling member with which the first coupling member can be coupled to
5 connect it to the vehicle, the vehicle comprising a chassis having a transverse beam situated at the rear side of the vehicle, the second coupling member being permanently or undetachably attached to the transverse beam.
2. Coupling assembly according to claim 1, the second coupling member
10 being welded fixed to the transverse beam.
3. Coupling assembly according to claim 1 or 2, the second coupling member being placed in the transverse beam.
- 15 4. Coupling assembly according to claim 3, the transverse beam being tubular having a first wall and an opposite second wall, the second coupling member being permanently or undetachably attached, such as by means of welding, to the first wall.
- 20 5. Coupling assembly according to claim 3 or 4, the transverse beam being tubular having a first wall and an opposite second wall, the second coupling member being permanently or undetachably attached, such as by means of welding, to the second wall.
- 25 6. Coupling assembly according to claim 4 or 5, the first wall and the second wall of the tubular transverse beam forming an upper wall and a lower wall,

respectively, of the transverse beam.

7. Assembly according to any one of the preceding claims, the second coupling member furthermore being provided with an eye for a hauling or
5 towing cable.

8. Coupling assembly according to claims 6 and 7, a third wall connecting the first and second wall of the transverse beam being provided with an opening for access to the eye, the eye preferably extending at least partially
10 through the opening to the outside.

9. Assembly according to any one of the preceding claims, the second coupling member being provided with a placement flange for abutment to the outside of the transverse beam, the flange being preferably at least almost
15 circumferential.

10. Assembly according to any one of the preceding claims, the second coupling member furthermore being provided with one or more means for attachment of a safety cable.
20

11. Assembly according to any one of the preceding claims, in which the first coupling member can be detachably coupled to the second coupling member.

25 12. Assembly according to any one of the preceding claims, the first coupling member being dividable into a first part that can be coupled to the second coupling member and a second part that can be connected to an operation member, such as a hitch ball.

30 13. Assembly according to claim 12, the second part being plate-shaped and provided with holes for bolts for attachment of the operation member.

14. Assembly according to claim 12, the second part defining an accommodation sleeve for accommodation of an insertion member of the operation member.

15. Assembly according to any one of the preceding claims, the second coupling member being made of steel, particularly metal, and obtained by injection moulding.

16. Assembly according to any one of the preceding claims, the first coupling member comprising an insertion member and the second coupling member comprising an accommodation member, in which the insertion member can be coupled in the accommodation member.

15 17. Vehicle having a chassis, the chassis being provided with a coupling member that is permanently fixed and undetachably connected to it, for detachable coupling to a further coupling member for a connection member for an accessory, such as a car trailer or bike rack, to be taken along by the vehicle, such as by towing or carrying.

20 18. Vehicle according to claim 17, the chassis comprising a transverse beam situated at the rear, the coupling member being fixedly attached to the transverse beam.

25 19. Vehicle according to claim 18, the coupling member being welded fixed to the transverse beam.

20. Vehicle according to claim 18 or 19, the transverse beam being tubular and the coupling member extending into the transverse beam.

30 21. Vehicle according to claim 20, the transverse beam being polygonal in cross-section, the coupling member being permanently or undetachably attached to at least two of the sides of the polygon.

22. Vehicle according to claim 19, the coupling member being welded fixed to the transverse beam, by means of a placement flange forming a unity therewith.

5

23. Vehicle according to any one of the claims 17-22, the coupling member furthermore being provided with an eye for a hauling or towing cable.

24. Vehicle according to any one of the claims 17-22, the coupling member furthermore being provided with one or more means for attaching a safety cable.

10

25. Coupling member suitable and intended for a coupling assembly according to any one of the claims 1-16.

15

26. Coupling assembly suitable and intended for an assembly according to any one of the claims 1-16.

27. Coupling member suitable and intended for a vehicle according to any one of the claims 17-24.

20

28. Assembly of a vehicle and a coupling assembly for it, the coupling assembly being provided with an eye for a hauling or towing cable.

29. Assembly according to claim 28, the coupling assembly furthermore being provided with one or more means for attaching a safety cable.

25

30. Assembly according to claim 28 or 29, the coupling assembly comprising a tow hitch.

30

31. Assembly according to claim 28, 29 or 30, the coupling assembly comprising a first coupling member provided with a connection member for a

car trailer or an accessory, such as a bike rack, and a second coupling member with which the first coupling member can be coupled to connect it to the vehicle, the eye and/or the means for attaching a safety cable forming a unity with the second coupling member.

5

32. Assembly according to claim 31, the vehicle comprising a chassis having a transverse beam situated at the rear side of the vehicle, the second coupling member being permanently or undetachably attached to the transverse beam.

10

33. Coupling assembly for vehicles, provided with one or more of the features as described in any one of the claims 28-32.

15

34. Coupling assembly provided with one or more of the characterising measures described in the attached description and/or shown in the attached drawings.

35. Vehicle provided with one or more of the characterising measures described in the attached description and/or shown in the attached drawings.

1/6




FIG. 1

2/6




FIG. 1A

3/6





FIG. 1B






FIG. 3A





FIG. 3B

6/6



INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 03/00645

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60D1/52 B60D1/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B60D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2 978 260 A (ULRICH HEBEISEN) 4 April 1961 (1961-04-04) column 1, line 15 -column 2, line 5; figures 1-3	1, 3, 17, 18
A		2, 4-16, 19-35
X	FR 2 637 847 A (RAPIDE) 20 April 1990 (1990-04-20) page 5, line 32 -page 6, line 6; figures 1-8	1, 3
A		17, 28
X	US 6 386 573 B1 (SOLOMON ROBERT J) 14 May 2002 (2002-05-14) column 2, line 16-38; figures 1-5	1
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

19 January 2004

Date of mailing of the international search report

26/01/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Kusardy, R

INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 03/00645

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 229 871 A (PORSCHE AG) 29 July 1987 (1987-07-29) figures 1-3 -----	1,2
A	DE 40 00 784 A (BOUMANS JOHANNES A) 19 July 1990 (1990-07-19) column 4, line 22-33; figure 1 -----	1
A	NL 1 008 215 C (BRINK BV) 6 August 1999 (1999-08-06) figures 1-3D -----	1
A	EP 0 950 549 A (ELLEBI S R L) 20 October 1999 (1999-10-20) cited in the application figures 1-6 -----	1

INTERNATIONAL SEARCH REPORT

Intel International Application No
PCT/NL 03/00645

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2978260	A	04-04-1961	NONE	
FR 2637847	A	20-04-1990	FR 2637847 A1	20-04-1990
US 6386573	B1	14-05-2002	AU 9714201 A CA 2363426 A1 EP 1219473 A2	13-06-2002 11-06-2002 03-07-2002
EP 0229871	A	29-07-1987	DE 3537305 A1 DE 3662998 D1 EP 0229871 A1	23-04-1987 01-06-1989 29-07-1987
DE 4000784	A	19-07-1990	NL 8900083 A DE 4000784 A1	01-08-1990 19-07-1990
NL 1008215	C	06-08-1999	NL 1008215 C1	06-08-1999
EP 0950549	A	20-10-1999	EP 0950549 A1 AT 208295 T DE 69802376 D1 DE 69802376 T2 ES 2163219 T3	20-10-1999 15-11-2001 13-12-2001 23-05-2002 16-01-2002